

TECHNICAL DATASHEET

ORI-C6

29-03-2022



VT/ORI-C6/18W/SMD/40K/22CM/IP65/ANTR/CB/BULKHEAD

NOTES

General Informations

Stock Code	2025640
HSC/GTIP Code	9405.10.91.50.00

Electrical Characteristics

Current Type	AC
Operation Voltage	220-240 Volt
Operation Frequency	50/60 Hertz
Electrical Current	0,17 Amper
Power	18 Watt
Power Factor	>0.5
Luminous Efficiency	73 lumen/Watt
Energy Savings	0,85
Dimmable	No
Electrical Protection Class	Class II

Electrical Component Specifications

Component Fitting Type	Internal Driver
Driver Properties	DOB
Driver Input Voltage	220-240 Volt

Lighting Characteristics

Luminous Flux	1314 lumen
Time for 60% of Lumen	<0.5 seconds
Light Beam Angle	120°
Flicker	No
LED Type	SMD
CCT	4000K

Mechanical Parameters

IP Protection Class	IP65
Switch On/Off Cycle	25000x
Lifetime	25000 hours
Body Material	ABS
Body Colour	Anthracite
Diffuser Material	PC
Mounting Accessories	Screws
Product Height	65 millimeter
Product Width	Ø220 millimeter
Ambient Temperature (Ta)	-20°C<Ta<50°C

Logistic Informations

Outbox Length	465 millimeter
Outbox Width	295 millimeter
Outbox Height	470 millimeter
Outbox Volume	0,064 cbm
Outbox Quantity	16 pieces
Unit Net Weight	0,42 kilogram
Outbox Net Weight	6,72 kilogram
Outbox Gross Weight	8,84 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.